

TACKY MAT STERILE

Technical Data 1

Materials:

Anti-bacteria wate-based adhesive+ PE film

Thickness:

0.035mm, 0.045mm, 0.05mm (customizable)

Color:

Blue/White/Grey/Green/Clear etc.

Normal Sizes:

26 ""*45 ", 24 ""*36 ", 18 ""*36 " (customizable)

Structure:

30 pages/mat (32 sheets in total)

Package:

4mats/case, 8 mats/case or 10 mats/case

Tackness :

Tackness of Page 1-29 (Top film): 400g/25mm (+/- 50)


depends on mat tackness level (we have high tack,

normal tack or low tack)

Tackness of Page 30 (Bottom film): 600g/25mm (+/-

50)

Product Picture



Description

Anti-bacterial tacky mat consists of multiple layers of clean film with even adhesive. It can effectively capture dirt and bacteria from foot-traffic and equipment wheels. Every thin film is covered with top-grade adhesive and anti-bacteria material, which can eliminate over 90% of bacteria and easily help you control your environment.

Structure

Mats consist of 1 layer of non-adhesive clear PE film, 29 layers of single coated PE film and 1 layer of double coated PE film.

Application

1. Best partner of cleanroom, laboratory and other sterilized/cleanroom environment.
2. Aerospace, biotech, laser optics, bio-pharmaceuticals.

Order Information

Serial Number	Checking Item	Standard	Testing Results
1	Lengthways Pulling Strength (Mpa)	≥10	20
2	Transverse Pulling Strength (Mpa)	≥8	17
3	Lengthways Breaking Elongation Rate (%)	≥150	585
4	Transverse Breaking Elongation Rate (%)	≥200	839
5	Sizing Condition	--	Glossy and uniform
6	Adherence in 180° angle (SS.G/25MM)	GB2792-81	400
7	Temperature Resistance Test	Q/DT1-2004	60
8	Antibacterial rate	--	> 90%